

FEC AerPPC Series



Side USB I/O for Add-on Devices



AerPPC PP-1635



Intergrated Customer Display



AerArm with 2nd Display

SPECIFICATIONS

Model	PP-1635
LCD Display	15" TFT LCD Panel
Resolution	1024 x 768
Touch Panel	P-CAP (10-points touch)
CPU	BayTrail Celeron J1900 2.0 - 2.4 GHz
RAM	4GB DDR3 (up to 8GB)
Storage	64GB SSD
Construction	Aluminum Die-casting + Plastic
Serial Port	4 x COM (RJ45 x 2, DB9 x 2)
USB Port	5 x USB (USB2.0 x 4, USB3.0 x 1)
Cash Drawer Port	1 x RJ11 (12V)
LAN Port	1 x RJ45 Gigabit LAN
Video Port	1 x VGA (12V optional Selectable in BIOS)
DC Input	1 x 12V DC
DC Output	1 x 12V DC
Power Supply	60W Adapter
Operation System	Windows 7, POSReady 7, Windows 10
Dimension (W x H x D)	366 mm x 335 mm x 220 mm

*Specifications are subject to change without notice.

AERPPC

Fanless All in one Panel PC: Featuring Intel Celeron J1900 quad-core CPU, the fanless 15" PP1635C is a perfect POS solution. With its small footprint, it also creates more space for work efficiency.

True flat P-CAP touch: Featuring elegant and graceful bezel-free design. The sensitivity of P-CAP touch fulfills customers' demands based on different user scenarios.

Aluminum Die-casting housing: It is not only robust and durable but also provides a great solution for heat dissipation for CPU, RAM, and storage.




ULTRA SLIM

The total thickness of PP-1635C is from 27.9 to 41.7mm. It is not only slim but also with strong and durable aluminum design to maximize your working space.



EASY SWAP STORAGE

Loose one single screw then you will be able to access the storage for easy maintenance.



CABLE MANAGEMENT

To avoid messy cabling in working area, we offer a solution that cables can be hidden within the back cover of the stand to make working area always clean and tidy.

